


SPECCRETE® ACCENT RELEASE POWDER



SAN DIEGO BUFF



MESA BUFF



SMOKE



ANTIQUE WHITE



COPPER



SANDSTONE



ADOBE BROWN



NATURAL



BRICK RED



YOSEMITE BROWN



LIGHT WALNUT



PEWTER



BAJA RED




PECAN TAN



KAILUA BROWN



CHARCOAL GRAY



RUSSETT



GREEN SLATE



DARK WALNUT



GRAPHITE BLACK

SPECCRETE® ACCENT RELEASE POWDER

PRODUCT DESCRIPTION: Speccrete® Accent Release Powder is a specially formulated pigmented powder designed to prevent freshly placed concrete from adhering to concrete texturing mats. Speccrete® Accent Release Powder transfers the details of the stamping mats to freshly placed concrete in matching or contrasting colors. Speccrete® Accent Release Powder is used on plain or integrally pigmented concrete and in combination with Speccrete® Dust-On Colored Hardener.

BENEFITS:

- **PROVIDES ACCURATE DETAIL TRANSFER**
- **PREVENTS ADHESION OF CONCRETE TO STAMPS OR TEXTURE MATS**
- **ALLOWS ANTIQUE EFFECT (DUAL COLOR TONE) ON SURFACE**

DIRECTIONS FOR USE: Place, screed and float the concrete surface as required. When excess moisture is no longer evident, broadcast Speccrete® Accent Release Powder in a thin uniform layer over the concrete surface to be textured. Texture mats may be placed immediately following the Accent Release Powder application. Removal of the excessive Speccrete® Accent Release Powder can take place after the concrete is sufficiently set and the surface can not be damaged. Excess material may be swept from the surface and residual Speccrete® Accent Release Powder may be removed by using a *low setting* pressure washer or *light* scrubbing. **Care must be taken to not remove the surface concrete during this step.** After the concrete is allowed to dry (24 hour minimum wait period is suggested), apply a clear, non-yellowing acrylic sealer such as Stampsheen 350 to protect and enhance the newly placed textured concrete.

COVERAGE: The amount of Speccrete® Accent Release Powder used depends upon the desired depth of the texturing mat impression and the degree to which the concrete has set. Approximate coverage rate is 3 pounds per 100 square feet.

CAUTIONS: Cover and protect all surrounding areas where color is not desired. Be aware of wind conditions when spreading Speccrete® Accent Release Powder. In colder temperatures allow more time for the concrete to cure before removing the Speccrete® Accent Release Powder. Be careful not to stain surrounding areas with excess rinse water during removal of residual Speccrete® Accent Release Powder. The use of Concrete Earth's Accent Release Liquid is recommended for applications requiring a monotone "neutral" surface, or for jobs where powders cannot be used due to the possible color contamination of surroundings or for interior projects where wash off and rinse down is not a viable option.

WARNINGS: Contains synthetic iron oxide powders, avoid inhalation of dust. Wear gloves, safety goggles, and OSHA-NIOSH approved dust respirator during placement. Refer to product M.S.D.S. (Material Safety Data Sheet) for additional safety information. Do not take internally. Avoid prolonged contact with skin. **FOR INDUSTRIAL USE ONLY. KEEP OUT OF REACH OF CHILDREN.**

NPCS-HMIS SAFETY RATINGS: HEALTH = 2, FLAMMABILITY = 0, REACTIVITY = 0, PROTECTION = E (Gloves, goggles, dust mask)

LIMITED WARRANTY: This product is warranted to be of merchantable quality when used according to the instruction herein. It is not warranted to be suitable for any purpose or use other than the general purpose for which it is intended. Liability under this warranty is limited to the replacement of the product as purchased, if found to be defective upon inspection by the manufacturer. This limited warranty is issued and accepted in lieu of all other expressed warranties and explicitly excludes liability for consequential damages. Buyer assumes all risk and liability resulting from the use of this product.



COLORED CONCRETE



STAMPS AND RELEASE



WASHED



FINISHED AND SEALED



Concrete Earth, LLC ~ Specco Industries, Inc.
13087 Main Street • Lemont • IL 60439 • (800) 441-6646
www.ConcreteEarth.com www.specco.com

A Complete Line of Quality Products for Concrete & Masonry since 1972

