

PALLET LUBE CONCENTRATE

WATER DILUTABLE RELEASE AGENT

PRODUCT DESCRIPTION: Specco Pallet Lube is a concentrated liquid solution containing linear alkyl sulfonates that is specifically formulated to create a barrier between the metal surface of the pallet and the concrete. Pallet Lube prevents the concrete from sticking to the pallet after steaming or curing and when tipped out. Additionally, Pallet Lube is a very effective release agent for the top ring, spindle and pallet of a concrete pipe machine reducing friction between turning parts. Pallet Lube is non-flammable, fully biodegradable, and non-corrosive and will not stain the finished product.

BENEFITS: PROMOTES EASY STRIPPING OF HEADER RINGS AND PALLETS...HELPS MINIMIZE CLEAN UP OF ZERO SLUMP MIXERS AND OTHER EQUIPMENT...VOC COMPLIANT IN ALL STATES

COMPOSITION: Combination of sulfonates & oleates with cleaning additives in water carrier.

PHYSICAL DATA:	APPROXIMATE VALUES @ 70° F (21° C):
Color:	Light blue green clear liquid
Solids:	25.0 +/-0.25%
Weight/gallon:	8.75 lbs./gallon +/- 0.10
pH:	10.50 +/- 0.20
V.O.C. levels:	15 g/L (0.13 lbs. /gal.)

VOC COMPLIANCE: Pallet Lube contains less than 250 g/L (2.08 lb. /gal.) volatile organic compounds. Meets existing form release agent VOC (VOM) regulations under the EPA's National AIM (Architectural and Industrial Maintenance) listings for all states including OTC, LADCO, CARB, and SCAQMD.

DIRECTIONS FOR USE: Surfaces should be clean, dry and free of contaminants. Apply a light coating of Pallet Lube using sprayer, rag or brush to the steel pallet trays, completely covering the entire surface. Pallet Lube may be diluted up to 1:2 with water (by volume) in typical applications for increased coverage and cost reduction.

CAUTIONS: Do not apply in temperatures below 35° F as this is a water-based product and subject to freezing. Wear eye and skin protection during placement. Keep from freezing. Allow pallet trays to dry before using.

WARNINGS: Do not use near unprotected food and drink. Provide adequate ventilation and fresh air during the application. User can refer to Pallet Lube M.S.D.S. (Material Safety Data Sheet) for any additional information before use. KEEP OUT OF REACH OF CHILDREN. FOR INDUSTRIAL USE ONLY

HMIS SAFETY CLASSIFICATIONS: Health =1, Fire = 0, Reactivity = 0, Personal Protection = C -Glasses, Gloves, Protective clothing

PACKAGING: 5 gallon (18.9 L), 55 gallon (208 L), and 265 gallon (1000 L) containers.

STORAGE: 40° to 90° F. KEEP FROM FREEZING

SHELF LIFE: 1 year properly stored

FREIGHT CLASS: ITEM 33880, Sub 2, LTL 55



LIMITED WARRANTY: This product is warranted to be of merchantable quality when used according to the instruction herein. It is not warranted to be suitable for any purpose or use other than the general purpose for which it is intended. Liability under this warranty is limited to the replacement of the product as purchased, if found to be defective upon inspection by the manufacturer. This limited warranty is issued and accepted in lieu of all other expressed warranties and explicitly excludes liability for consequential damages. Buyer assumes all risk and liability resulting from the use of this product.

Revised – 11-14-08