

SPECCO GRIP

SLIP RESISTANT ADDITIVE FOR CONCRETE SEALERS

PRODUCT DESCRIPTION: Specco Grip is a micronized polymeric powder which can be added to concrete sealers to improve slip resistance. Specco Grip is of low density, lightweight composition which helps eliminate settling in low viscosity (thin) sealers or stains. Specco Grip has a round spherical shape which provides optimum abrasion resistance, gloss control, and is less abrasive when compared to silica based texturizing agents. Specco Grip can be added to “film forming” acrylic sealers including Specco’s waterbased Envirocure 309 & 1315 and Envirosheen, as well as Specco’s solvent based acrylics which include C-15, Supersheen, Pebblesheen, Pavesheen and Stampsheen. Typical applications include patios, pool surrounds, sidewalks, porches, walkways, inclines, or garage floors.

BENEFITS: PROVIDES IMPROVED ABRASION RESISTANCE WITH INCREASED COEFFICIENT OF FRICTION...SPHERICAL SHAPE ALLOWS EASY CLEANING OF THE SURFACE ...PROVIDES A SOFTER FEEL TO BARE FEET VERSUS SILICA SAND OR ABRASIVES...DOES NOT INCREASE VISCOSITY...WILL NOT YELLOW OR ALTER FINAL SURFACE COLOR

COMPOSITION: Medium-fine mesh, polypropylene based powder

PHYSICAL PROPERTIES @ 70° F (21° C) (APPROXIMATE):

Mesh size	50
Particle size	Average = 160-180 microns, maximum = 300 microns
Melt point	167 degrees C
Density	0.90 g/cc

PACKAGING / COVERAGE: Specco Grip is available in one package size, 16.0 ounce (1.0 lb) for addition to 5 gallons of sealer. For applications in-between 5 gallon increments, add or subtract 3.2 ounce (0.2 lb) of Specco Grip per gallon of sealer. Specco Grip can be added to a maximum of 8.0 ounce per gallon if higher levels of slip resistance are required. Small test applications should be made on questionable substrates to check visual aesthetics and degree of slip resistance provided.

APPLICATION / MIXING: Add 16.0 ounces (1 bottle) of Specco Grip into one five gallon pail of the selected Specco stain or sealer and apply the mixed material per the manufacturer’s normal instructions. Specco Grip may float initially, but will wet out and mix in easily with slight mixing and agitation. During application, occasional mixing is recommended to keep all the particles suspended evenly in the solution.

CAUTIONS: Specco Grip provides increased slip resistance and improved surface texture to Specco’s various stains and sealers, however the resulting finish should not be mistaken as either a “non-skid” or “non-slip” surface. Specco Grip is not recommended for addition to wood stains or water repellents. Specco Grip’s small particle size will limit its slip resistant effectiveness on heavy bodied (viscous) epoxies or hi build coatings. Specco Grip may slightly reduce the degree of reflection “wet look sheen” on high gloss acrylics such as Specco Pavesheen or Envirosheen due to light defraction of the additive. When applying Specco Grip modified sealers or stains by roller, it is recommended not to “re-roll” wet areas for proper surface uniformity.

WARNINGS: Specco Grip is silica free and is of a non hazardous composition. When mixing Specco Grip, the use of an OSHA or NIOSH approved dust mask or respirator is recommended due to residual dusting generated during the mixing process. Allow adequate ventilation during use. Refer to product M.S.D.S. (Material Safety Data Sheet) for additional safety information. Do not take internally. FOR INDUSTRIAL USE ONLY.

WARNINGS(Continued): KEEP OUT OF REACH OF CHILDREN. If inhalation or exposure causes any physical discomfort or irritation that persists, SEEK MEDICAL ATTENTION.

NPCS HMIS SAFETY RATINGS: HEALTH = 1, FLAMMABILITY = 1, REACTIVITY = 0, P. PROTECTION = E

STORAGE: 40° to 90° F

SHELF LIFE: 1 year properly stored

FREIGHT CLASS: Class 50

LIMITED WARRANTY: This product is warranted to be of merchantable quality when used according to the instruction herein. It is not warranted to be suitable for any purpose or use other than the general purpose for which it is intended. Liability under this warranty is limited to the replacement of the product as purchased, if found to be defective upon inspection by the manufacturer. This limited warranty is issued and accepted in lieu of all other expressed warranties and explicitly excludes liability for consequential damages. Buyer assumes all risk and liability resulting from the use of this product.

Revised – 03-08