

# **U-MIX® PUMP FLUSH**

## **CLEANING/LINE PURGING LIQUID FOR URETHANE PUMP EQUIPMENT**

**PRODUCT DESCRIPTION:** Specco U-Mix® System Flush is an odorless, non-flammable, non-toxic solution, designed to thin and flush residual U-Mix® Polyurethane resin from the injection pump system used to place the urethane grout material. Specco U-Mix® System Flush will not harm pump rings or hoses and may be left in the pump after thoroughly flushing the system.

**BENEFITS:** SINGLE COMPONENT...NON-FLAMMABLE...WILL NOT FREEZE.

<b>PHYSICAL PROPERTIES at 70° F (21° C):</b>	<b>APPROXIMATE VALUES:</b>
<b>Weight per Gallon (mixed):</b>	8.20 +/- 0.1 lb./ gallon
<b>Color/odor:</b>	Clear liquid with no noticeable odor
<b>Viscosity-Brookfield:</b>	75 cps +/- 10cps
<b>Flash Point:</b>	>440° F (227° C)-open cup method
<b>V.O.C. Content (% Volatiles):</b>	<1% -Contains no VOC components per EPA Method 24

**DIRECTIONS FOR USE:** Circulate Specco U-Mix® System Flush through the equipment until the solution shows clear in color. Valves, springs, bearings and other working parts of the injection system may be soaked in U-Mix® System Flush to clean and help lubricate.

**WARNINGS:** Avoid contact with skin and eyes. Wear protective clothing and safety glasses during application. Keep away from food and drink. Do not take internally. Refer to product M.S.D.S. (Material Safety Data Sheet) for further health and safety information. FOR INDUSTRIAL USE ONLY. KEEP OUT OF REACH OF CHILDREN.

**H.M.I.S. CODES:** HEALTH = 1, FLAMMABILITY = 0, REACTIVITY = 0, PERSONAL PROTECTION = C (GLOVES, GOGGLES, APRON)

**SHIPPING NAME:** Plasticizer / Pump Lubricant – Not regulated

**SHIPPING CLASS:** ITEM 33880, SUB 2, LTL 55

**PACKAGING:** 1gallon (3.78 L), 5 gallon (18.9 L) and 55 gallon (208 L) containers.

**STORAGE:** 40° to 90° F

**SHELF LIFE:** 1 year properly stored

**LIMITED WARRANTY:** This product is warranted to be of merchantable quality when used according to the instruction herein. It is not warranted to be suitable for any purpose or use other than the general purpose for which it is intended. Liability under this warranty is limited to the replacement of the product as purchased, if found to be defective upon inspection by the manufacturer. This limited warranty is issued and accepted in lieu of all other expressed warranties and explicitly excludes liability for consequential damages. Buyer assumes all risk and liability resulting from the use of this product.

Revised – 01-07