



CEMENT BUSTER

EQUIPMENT CLEANER & CEMENT SCALE REMOVER

PRODUCT DESCRIPTION: *Specco Cement Buster C-50* is a concentrated cleaning solution made from a combination organic and inorganic acids and penetrating surfactants. *Cement Buster C-50* is formulated to ease removal of hardened concrete from mixers, forms, tools, trucks and related equipment. The use of *Cement Buster C-50* will accelerate the removal of concrete laitance from equipment normally requiring sandblasting or jack hammering techniques.

BENEFITS:

- **Fast acting powerful formulation dissolves heavy cement scale and build up**
- **Will not harm painted machinery, rubber, or chrome**
- **Bio-degradable formulation**

COMPOSITION: Proprietary pH buffered acid blend with surfactants

LEED CREDIT CONSIDERATIONS: Materials and Resources: **MR Credit 5.2:** Regional materials- Greater than 20% extracted, processed and manufactured regionally at production location: Kankakee, IL. 60901. 90% Content- Harvested within 500 miles.

PHYSICAL PROPERTIES at 70° F (21°C):	APPROXIMATE VALUES:
Weight per gallon:	9.76 +/- 0.50 lb./ gallon
pH:	4.00 +/- 0.50
Color:	Clear yellowish-brown liquid
Viscosity –Brookfield:	10 cps

DIRECTIONS FOR USE: Use *Cement Buster C-50* “as is” for removal of any cement scale build-up. Do not dilute. Adding water to the *Cement Buster C-50* will greatly reduce its removal ability and effectiveness.

APPLICATIONS: Apply *Cement Buster C-50* to the contaminated surface with a masonry washing brush or sprayer and scrub the solution into the stained area. The concrete surface must be completely saturated. *Cement Buster C-50* will react with the cement initially with a foaming action, but should be allowed to re-act and work into the substrate for a minimum of 30 minutes. All applications must then be carefully removed by using a pressure washer or mechanical scraping tools. *Cement Buster C-50* can be left on the surface overnight, but should be re-applied in the morning to reactivate the softening process. Thicker concrete build-up of 1/4 inch or more will most likely require multiple applications. Repeat the procedure if necessary.

COVERAGE: Approximately **100 square feet per gallon**

CAUTIONS: Always test an area before overall application to determine suitability and results. It is recommended to run pressure washers at as low a setting as possible to avoid any consequential pressure related paint peeling damage to equipment.

GHS HAZARD RATINGS: DANGER:



601 NORTH 5TH AVE • KANKAKEE, IL • 60901
630-257-5060 SPECCO.com





Irritant: Respiratory Tract Irritation.



Health Hazard: Corrosive Material

WARNINGS: HEALTH HAZARD & IRRITANT: Refer to product S.D.S. (SAFETY DATA SHEET) for FIRST AID INFORMATION, or any related health and safety information before using this product. For medical emergencies only, call INFOTRAC @ 800-535-5053.

Cement Buster C-50 is an acidic based solution and can cause severe burns. Use with OSHA/NIOSH approved eye protection. Wear protective safety glasses, gloves, and clothing when handling. Refer to product S.D.S. (Safety Data Sheet) for detailed health and safety information. Protect all grass, foliage and related landscaping from contact with Cement Buster C-50. Keep all traffic off the treated surface until dry. Keep containers closed when not in use and dispose of accordingly in accordance with local, state, and federal regulations. Keep away from food and drink. Do not take internally. **FOR INDUSTRIAL USE ONLY. KEEP OUT OF REACH OF CHILDREN.**

H.M.I.S. CODES (Hazardous Materials Identification System): HEALTH = 3, FLAMMABILITY = 0, REACTIVITY = 0, PERSONAL PROTECTION = C (Rubber Gloves and Safety Goggles).

SHIPPING NAME: Mixture: contains Phosphoric Acid, CAS # 7664-38-2 –regulated by D.O.T.

SHIPPING CLASS: UN1805, Phosphoric Acid Solution, CORROSIVE LIQUID, HC 8, PG III
Item #44155 Sub 2 Freight Class 77.5- Concrete & Masonry Cleaning Solution-Acid Based

STORAGE: Ideal storage is between 60° to 80° F. Keep from freezing.

SHELF LIFE: 3 years stored properly. Depending on storage conditions, the shelf life may be extended.

PACKAGING: 1 gallon, 5 gallon, 55 gallon containers

WARRANTY: Specco Industries Inc (Specco) solely and expressly warrants that its products shall be free from defects in materials and workmanship for one (1) year from the date of purchase. Unless authorized in writing by an officer of Specco, no other representations or statements made by Specco or its representatives, in writing or orally, shall alter this warranty. **SPECCO MAKES NO WARRANTIES, IMPLIED OR OTHERWISE, AS TO THE MERCHANTABILITY OR FITNESS FOR ORDINARY OR PARTICULAR PURPOSES OF ITS PRODUCTS AND EXCLUDES THE SAME.** If any Specco product fails to conform with this warranty, Specco will replace the product at no cost to Buyer. **Replacement of any product shall be the sole and exclusive remedy available and buyer shall have no claim for incidental or consequential damages.** Specco does not authorize anyone on its behalf to make any written or oral statements which in any way alter Specco's installation information or instructions in its product literature or on its packaging labels. **Specco explicitly excludes any written or oral statements or implied warranty on the performance of an applied/installed product manufactured or sold by or through Specco. Specco has no control over Specco application standards adherence, site conditions, atmospheric variations, installer/applicator skill level or the determination of the suitability of any Specco products for a specific intended purpose. Buyer shall be solely responsible for determining the suitability of Specco's products for the Buyer's intended purposes.** Product demonstrations, if any, are done for illustrative purposes only and do not constitute a warranty or warranty alteration of any kind.

Revised 08-27-19



601 NORTH 5TH AVE • KANKAKEE, IL • 60901
630-257-5060 SPECCO.com

